



Product: Defender Short Shift Handle

Disclaimer: N/A

Instructions:

- Pull down the rubber boot on the shifter handle and loosen the jam nut under the shifter handle end. Spin off and remove the shifter handle knob, jam nut, and slide the rubber boot off of the shifter handle.



Thank you for your purchase.

For a list of more products we offer please visit marqcadeng.com or message us on facebook at marqCAD Engineering if you don't see what you are looking for on the website.

- Remove the plastic shift gate by removing the two screws and sliding it up over the shifter handle.



- Loosen and remove the bolt that holds the stock shifter. When removing take note on the orientation of the spring and how it locks onto the bracket to keep tension on the shifter. It will need to be installed in the same way so functionality remains the same.



Thank you for your purchase.

For a list of more products we offer please visit marqcadeng.com or message us on facebook at marqCAD Engineering if you don't see what you are looking for on the website.

- The metal bushing sleeve from the stock shift handle will not be used on the new shifter. Reinstall the shifter in the opposite order of removal using the stock hardware. Shifter bend should be as shown in the picture below.



- Reinstall the plastic shift gate and make sure the shifter functions as it should. Install the lock nut and shift handle.



Thank you for your purchase.

For a list of more products we offer please visit marqcadeng.com or message us on facebook at marqCAD Engineering if you don't see what you are looking for on the website.