



Product: Garmin Tread 5.5" Defender Mount

Disclaimer: N/A

Instructions:

- Remove the stock mount from the charger base by removing the 4 screws. Take the nylock nuts from the backside of the screws and press them into the backside of the defender holder, then install the charging base into the defender holder with the 4 screws removed.



- Line the mount up to the top header panel to locate where a hole should be drilled to run the power wires from the acc. Terminal to the GPS and the antenna wire. Once marked pull the header panel down by removing the 2 outer screws from each end and the 4 screws from the center.



Thank you for your purchase.

For a list of more products we offer please visit marqcadeng.com or message us on facebook at marqCAD Engineering if you don't see what you are looking for on the website.

- Run the power wires and antenna wires how you want. This will depend on where you mount your antenna, make sure there is enough wire to reach where you are mounting. Once wires are situated feed them through the hole made in the marked location and re-install the header panel using the hardware that was removed.



- Run the wires down into the GPS holder and connect them to the charging base. It may be easiest to run the handset wire and connect that at this time as well if you are using it.



Thank you for your purchase.

For a list of more products we offer please visit marqcadeng.com or message us on facebook at marqCAD Engineering if you don't see what you are looking for on the website.

- Place the holder in the mounting location, and secure it using the 4 supplied Phillips screws.



- GPS Installation and Removal
 - To install slide the bottom of the GPS into the holder and latch it to the bottom side of the charging base same as you would attach it not in the housing.



- By pushing on the top corners with even pressure, push the GPS top into the holder to lock it into the charging base. This may take some pressure to push it past the bottom edge.



Thank you for your purchase.

For a list of more products we offer please visit marqcadeng.com or message us on facebook at marqCAD Engineering if you don't see what you are looking for on the website.

- To remove use a tool of some kind to depress the release on the charging base through the top hole on the housing. Once depressed push on the bottom of the holder to have the opposite affect as when you installed the holder to get it past the bottom edge.



- Once the top side has popped out then push the GPS down slightly to get it off the bottom lock on the Charger base and then pull it out of the housing.

Thank you for your purchase.

For a list of more products we offer please visit marqcadeng.com or message us on facebook at marqCAD Engineering if you don't see what you are looking for on the website.